



2" Ø HOLE IN SHELF (TYP. 2)

38"

35"

PLAN VIEW

IMPORTANT NOTE - VERIFY BOOTH DESIGN IS COMPATIBLE WITH ON SITE CONDITIONS FOR PROPER ACCESSIBILITY.

NOTE : CLEAR DOOR OPENING TO BE 32"



STANDARD FEATURES DESIGNED INTO BOOTH TO MEET ADA GUIDELINES.

- * MANEUVER WITHIN BOOTH - 60" DIAMETER
- * DOOR CLEARANCES - 32" CLEAR OPENING, 1/2" HIGH THRESHOLD
- * SHELF - 32" A.F.F.
- * CASHIER WINDOW - 33" A.F.F.
- * CEILING HEIGHT - 80" min.

(ACCESSIBLE ROUTE TO BOOTH - BOOTH CAN BE DESIGNED TO MEET ON SITE CONDITIONS, EXAMPLE: DOOR LOCATION AND THRESHOLD HEIGHT)

DURASTEEL MODEL PC-DAR157SL BUILDING NOTES :

- ① 100 AMP SINGLE PHASE 12 CIRCUIT LOAD CENTER W/MAIN BKR.
 - ② 115V DUPLEX, 230V OUTLET
 - ③ 64 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
 - ④ 34 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
 - ⑤ 22" DEEP SHELF
- * 3" OVERHANG EXTERIOR MEMBRANE ROOF
 - * 1- HEAVY DUTY ALUMINUM DOOR W/HALF GLASS AND ADA HANDLES
 - * 1- HEAVY DUTY ALUMINUM DOOR (SOLID) W/ADA HANDLES
 - * 1- HEAVY DUTY ALUMINUM DOOR (SOLID) W/LEVER LOCK
 - * GLAZING- CLEAR TEMPERED GLASS
 - * INSULATION- WALLS R-9, CEILING R-17
 - * ALUMINUM TREAD PLATE FLOOR
 - * BUILDING PAINTED- ADVISE COLOR
 - * UL LABEL FOR COMPLIANCE WITH THE N.E.C.

NOTES:

SLIDING DOORS AVAILABLE BOTH SIDES- SUFFIX DSL

CASHIER WINDOW AVAILABLE IN DOOR- SUFFIX CSL

PORTA-KING BUILDING SYSTEMS

4133 SHORELINE DRIVE EARTH CITY, MISSOURI 63045
 1-800-456-6464 FAX 314-291-2857 www.portaking.com

TITLE DURASTEEL MODEL PC-DAR157SL