

2"Ø HOLE IN SHELF (TYP. 2)

IMPORTANT NOTE— VERIFY BOOTH DESIGN IS COMPATIBLE WITH ON SITE CONDITIONS FOR PROPER ACCESSIBILITY.

PLAN VIEW

DURALUMINUM MODEL DAB8866SW BUILDING NOTES :

- ①— 100 AMP SINGLE PHASE 12 CIRCUIT LOAD CENTER W/MAIN BKR.
- ②— 115V DUPLEX, 230V OUTLET
- ③— 34 WATT SURFACE MTD. FLUORESCENT LIGHT
- ④— 22" DEEP SHELF
- * 3" OVERHANG EXTERIOR MEMBRANE ROOF
- * 1— HEAVY DUTY ALUMINUM DOOR W/HALF GLASS AND LEVER LOCK
- * GLAZING— CLEAR TEMPERED GLASS
- * ALUMINUM TREAD PLATE FLOOR
- * UL LABEL FOR COMPLIANCE WITH THE N.E.C.




STANDARD FEATURES DESIGNED INTO BOOTH TO MEET ADA GUIDELINES.

- * MANEUVER WITHIN BOOTH— 60" DIAMETER
- * DOOR CLEARANCES— 32" CLEAR OPENING, 1/2" HIGH THRESHOLD
- * SHELF— 32" A.F.F.
- * CASHIER WINDOW— 33" A.F.F.
- * CEILING HEIGHT— 80" min.

(ACCESSIBLE ROUTE TO BOOTH— BOOTH CAN BE DESIGNED TO MEET ON SITE CONDITIONS, EXAMPLE: DOOR LOCATION AND THRESHOLD HEIGHT)

NOTES:
SLIDING DOORS AVAILABLE BOTH SIDES— SUFFIX DSL
CASHIER WINDOW AVAILABLE IN DOOR— SUFFIX CSL

 <p>PORTA-KING BUILDING SYSTEMS</p>	
<p>4133 SHORELINE DRIVE 1-800-456-5464 FAX 314-291-2857 www.portaking.com</p>	<p>EARTH CITY, MISSOURI 63045</p>
<p>TITLE: DURALUMINUM MODEL DAB8866SW</p>	