



2" Ø HOLE IN SHELF (TYP. 2)

IMPORTANT NOTE- VERIFY BOOTH DESIGN IS COMPATIBLE WITH ON SITE CONDITIONS FOR PROPER ACCESSIBILITY.

PLAN VIEW

STANDARD FEATURES DESIGNED INTO BOOTH TO MEET ADA GUIDELINES.

- \* MANEUVER WITHIN BOOTH- 60" DIAMETER
- \* DOOR CLEARANCES- 32" CLEAR OPENING, 1/2" HIGH THRESHOLD
- \* SHELF- 32" A.F.F.
- \* CASHIER WINDOW- 33" A.F.F.
- \* CEILING HEIGHT- 80" min.

(ACCESSIBLE ROUTE TO BOOTH- BOOTH CAN BE DESIGNED TO MEET ON SITE CONDITIONS, EXAMPLE: DOOR LOCATION AND THRESHOLD HEIGHT)

DURASTEEL MODEL DAR147SL BUILDING NOTES :

- 100 AMP SINGLE PHASE 12 CIRCUIT LOAD CENTER W/MAIN BKR.
  - 115V DUPLEX, 230V OUTLET
  - 64 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
  - 34 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
  - 22" DEEP SHELF
- \* 3" OVERHANG EXTERIOR MEMBRANE ROOF
  - \* 1- HEAVY DUTY ALUMINUM DOOR W/HALF GLASS AND ADA HANDLES
  - \* 1- HEAVY DUTY ALUMINUM DOOR (SOLID) W/ADA HANDLES
  - \* GLAZING- CLEAR TEMPERED GLASS
  - \* INSULATION- WALLS R-10, CEILING R-19
  - \* ALUMINUM TREAD PLATE FLOOR
  - \* BUILDING PAINTED- ADVISE COLOR
  - \* UL LABEL FOR COMPLIANCE WITH THE N.E.C.

NOTES:  
 SLIDING DOORS AVAILABLE BOTH SIDES- SUFFIX DSL  
 CASHIER WINDOW AVAILABLE IN DOOR- SUFFIX CSL

**PORTA-KING** BUILDING SYSTEMS

4133 SHORELINE DRIVE EARTH CITY, MISSOURI 63045  
 1-800-456-5464 FAX 314-291-2857 www.portaking.com

TITLE DURASTEEL MODEL DAR147SL