

IMPORTANT NOTE - VERIFY BOOTH DESIGN IS COMPATIBLE WITH ON SITE CONDITIONS FOR PROPER ACCESSIBILITY.

NOTE : CLEAR DOOR OPENING TO BE 32"

NOTE : CLEAR DOOR OPENING TO BE 32"

PLAN VIEW

DURASTEEL MODEL DARI57SL BUILDING NOTES :


- ① 100 AMP SINGLE PHASE 12 CIRCUIT LOAD CENTER W/MAIN BKR.
- ② 115V DUPLEX, 230V OUTLET
- ③ 64 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
- ④ 34 WATT SURFACE MTD. FLUORESCENT LIGHT W/SWITCH
- ⑤ 22" DEEP SHELF

- * 3" OVERHANG EXTERIOR MEMBRANE ROOF
- * 1- HEAVY DUTY ALUMINUM DOOR W/HALF GLASS AND ADA HANDLES
- * 1- HEAVY DUTY ALUMINUM DOOR (SOLID) W/ADA HANDLES
- * 1- HEAVY DUTY ALUMINUM DOOR (SOLID) W/LEVER LOCK
- * GLAZING- CLEAR TEMPERED GLASS
- * INSULATION- WALLS R-10, CEILING R-19
- * ALUMINUM TREAD PLATE FLOOR
- * BUILDING PAINTED- ADVISE COLOR
- * UL LABEL FOR COMPLIANCE WITH THE N.E.C.



STANDARD FEATURES DESIGNED INTO BOOTH TO MEET ADA GUIDELINES.
 * MANEUVER WITHIN BOOTH- 60" DIAMETER
 * DOOR CLEARANCES- 32" CLEAR OPENING, 1/2" HIGH THRESHOLD
 * SHELF- 32" A.F.F.
 * CASHIER WINDOW- 33" A.F.F.
 * CEILING HEIGHT- 80"min.
 (ACCESSIBLE ROUTE TO BOOTH- BOOTH CAN BE DESIGNED TO MEET ON SITE CONDITIONS, EXAMPLE: DOOR LOCATION AND THRESHOLD HEIGHT)

NOTES:
 SLIDING DOORS AVAILABLE BOTH SIDES- SUFFIX DSL
 CASHIER WINDOW AVAILABLE IN DOOR- SUFFIX CSL


PORTA-KING BUILDING SYSTEMS
 4133 SHORELINE DRIVE EARTH CITY, MISSOURI 63045
 1-800-456-5464 FAX 314-291-2857 www.portaking.com

TITLE DURASTEEL MODEL DARI57SL